### **Borough of Woodcliff Lake**

188 Pascack Road, Woodcliff Lake NJ 07677

## <u>Application - Certificate of Continued Occupancy - Residential</u>

General Ordinance #131-5

### FORM MUST BE SUBMITTED NO LESS THAN 20 DAYS PRIOR TO CLOSING DATE

#### A Certificate of Occupancy shall expire ninety (90) days from issuance

Building Department: 201-391-4977 ext. 209/210

Property Address:				
Block:	Lot: Closing Date:			
Single Family (\$100):		Two-Family (\$150	)):	Other:
Name (Owner/Seller):				
Address (Current):				
Best Contact #:		Email:		
Seller Attorney Name:				
Attorney's Address:				
Attorney Phone #:		Email:		
Buyer Attorney Name: _				
Attorney's Address:				
Attorney Phone #:		Email:		
re-inspection will take  Please contact the Builto your scheduled inspection  Legible house number from the street, prior to Verify Sump Pumps and Verify that Boilers, Ho  Dead Bolts on the from	place, if need lding Departmoection. The sare also rection in your inspective not piped in the Water Heater the door must be	ed, for a \$50.00 fee. ent to confirm all conquired. Please make tion. Ito the sanitary sewers and Water Soften e keyless on the inte	nstruction permit sure that these er system and are ers obtained requerior side of the de	ired permits.
SELLER'S SIGNATURE:				
	I	FOR OFFICE USE ONI	LY	
Application Date:	F	ees:	Check #	Cash:

Distribution: Construction/Zoning (Original), Assessor, Collector, DPW, Police

# REQUIREMENTS FOR SMOKE DETECTOR, CARBON MONOXIDE DETECTOR AND FIRE EXTINGUISHER

- Smoke detectors are located on every level of the residence, including the basement
- Smoke detectors and Carbon Monoxide detectors are located within 1 O feet of all sleeping areas
- All Smoke Detectors and Carbon Monoxide Detectors are in working order
- All Smoke Detectors must be UL approved and have a 10 year sealed battery
- AC powered single or multiple station or multiple station smoke alarms installed as part of the original construction or rehabilitation project shall not be replaced with battery powered smoke alarms (Jan 2019, NJAC 5:70-4.19)
- All Carbon Monoxide Detectors with a manufacture date greater than 5 years must be replaced
- One 2A:10B:C rated fire extinguisher weighing less than ten (10) pounds should be located within 10 feet of the kitchen
- The bracket supplied by the manufacturer with the fire extinguisher must be used
- The extinguisher must be near a path of egress, accessible and visible
- The extinguisher must be installed with the operating instructions clearly visible during inspection and left for the new occupant
- The extinguisher should be serviced and tagged by certified Division of Fire Safety contractor within the past 12 months, or the seller must have a receipt for a recently purchased extinguisher
- See attached diagram for location instructions